



Specifications

Apple MessagePad





Note: Unless noted in the specifications subheading, product specifications are the same for both the Apple MessagePad 2000 and the Apple MessagePad 2100.





Processor

CPU

StrongARM SA-110 RISC processor
162 MHz





Memory

**Apple MessagePad
2000 RAM**

4 MB

**Apple MessagePad
2100 RAM**

8 MB

ROM

8 MB mask ROM





I/O Interface

Serial

One Newton InterConnect docking port supports serial I/O, audio I/O, and telephone I/O for networking and communications expansion

PCMCIA

Two Type II slots: 3.3 V and 5 V operation





Sound and Video

Speaker

8 ohm

Video Display

Transreflective LCD with EL backlight
480 x 320 pixels





Electrical

Main Batteries

4 AA alkaline batteries or a rechargeable NiMH battery pack





Physical

Dimensions

Height: 210.3 mm (8.25 in)

Width: 118.7 mm (4.7 in)

Depth: 27.5 mm (1.25 in)

Weight

Less than 1.8 lb with NiMH battery pack installed





Environmental

Temperature

Operating: 0 to 40°C (32 to 104°F)

Storage: -20 to 60°C (-3 to 140°F)

Relative Humidity

5% to 95% noncondensing

Operating Altitude

0-10,000 ft. (0 to 3048 m)

